

SP-L31

- Light weight for taking conveniently
- Multi-interface and different paper size support
- LCD display
- Super battery capability
- Continuing printing when battery in charging



Specification:

| | | |
|--------------------------|--------------------------|---|
| Print | Printing Method | Thermal Line |
| | Printing Speed | 80mm/s (Thermal Paper) 70mm/s (Label Paper) |
| | Effective Printing Width | 72mm/48mm/37.5mm |
| Paper | Paper Type | Thermal Paper/Label paper |
| | Paper Width | 80 mm±0.5mm、58mm±0.5mm、 44mm±0.5mm |
| | Paper Roll Diameter | 40mm (Max.) |
| | Paper Supply Method | Drop-in easy paper loading |
| Emulation | | CPCL/ESC-POS |
| Barcode | | 1D: EAN-13, EAN-8, UPC-A, UPC-E, CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25 2D: PDF417、QRCODE、DATA Matrix |
| Interface | | USB+Bluetooth (BT 2.0/BT4.0/both) |
| Battery | | DC7.4V,1.4A rechargeable Li-ion |
| Charger | | DC8.4V/0.8A |
| Printer Dimension(WxLxH) | | 109x105x51mm |
| Environment | Operating Temp | 0-50 °C |
| | Storage Temp | -20-60°C |
| | Operating Humidity | 10%-80% |
| | Storage Humidity | 10%-90% |
| Accessories | | Battery, Charger, USB Cable,CD Driver, Carrying Case and Paper-roll Option: vehicle charger |