

# SPRT POS 901



<b>Printing Method</b>	Thermal Line
<b>Resolution</b>	8 dots/ mm, 576 dots/ line
<b>Effective Printing Width</b>	72 mm
<b>Printing Speed</b>	170 mm/s
<b>Character Set</b>	ASCII, GB18030 (Chinese), BIG5
<b>Self-defined Character</b>	YES
<b>Print Font</b>	Codepage, ANK: 12 x24; Chinese: 24 x 24
<b>Barcode</b>	1D: UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128, 2D:PDF417,QR CODE, DATA matrix
<b>Graphic</b>	Support bitmap downloading
<b>Memory Printing</b>	YES
<b>Paper End Sensor</b>	YES
<b>Overheating Protection</b>	YES
<b>Interface</b>	RS232+USB+Ethernet
<b>Cash drawer control</b>	DC24V,1A, 6PIN RJ-11Socket
<b>Power Supply (Adapter)</b>	AC100 ~240V ± 10%(include) DC 24V, 2A
<b>TPH</b>	100 KM
<b>Auto Cutter</b>	1,000,000 cuts
<b>Paper Type</b>	Thermal paper
<b>Paper Width</b>	79.5± 0.5mm
<b>Paper Thickness</b>	0.06 to 0.08mm
<b>Paper Roll Diameter</b>	Max. 80mm
<b>Auto Cutter</b>	Partial Cut
<b>Operating Temp/Humidity</b>	0-50°C/10%-80%
<b>Storage Temp/Humidity</b>	-20-60°C / 10%-90%
<b>Dimension (LxWxH)</b>	160 x156 x 210 mm

- \* Zumbador Opcional
- \* Soporte opcional para instalación en pared

DATA PROF ESPAÑA S.A.  
C/Santa Leonor 63 2ºI  
28037 MADRID  
Teléfono: 913274647